



1 to accommodate and mate with said ribbed edge of any said cap on said jar; said  
2 handle accepts and permanently retains one end of said strap on one side of said  
3 handle while said handle also accepts and releasably secures the opposite end of  
4 said strap onto the opposite side of said handle.

5 4. The invention as claimed in claim 1 wherein said gripping strap means-, is  
6 wide enough so as to accommodate any side cap; said adjustable strap is long  
7 enough so as to accommodate any size cap while wrapping around said complete  
8 cap of said jar and return to said handle thereafter being secured onto said handle  
9 by releasable securing means; said length is preferred to be 12 inches having been  
10 selected from a range between 6 inches to 20 inches in said length; while the inside  
11 of said strap has a ribbed gripping texture so as to align, mate and grip with said  
12 ribbed surface of said cap, while one end of said strap permanently attaches to  
13 said handle and the opposite end releasably attaches to said handle; said strap is  
14 selected from a rubber, plastic or nylon material.

15 5. The invention as claimed in claim 1 wherein said opener has a preferred list  
16 of component parts comprising;

- 17 (1) A gripping handle;  
18 (2) An adjustable strap;  
19 (3) A permanent attachment means for one end of said strap to said handle;  
20 (4) A releasable securing means for the opposite end of said strap to said handle.

21 6. The invention as claimed in claim 1 wherein said jar opener has a method of  
22 use sequence for removing said cap of any said jar:

- 23 (a) Wrap the provided strap around the outer edge of the cap on the jar;  
24 (b) Secure the strap back onto the opposite side of the handle;  
25 (c) Grasp the present invention by the handle with one hand;  
26 (d) Grasp and stabilize the selected jar with the opposite hand;

27

28

1 (e) Push the handle in a counter clockwise direction until the cap is in the open  
2 position;

3 (f)Release the strap from the handle securing means thereby also releasing the cap  
4 from within the grasp of the strap; said invention thereby creates a functional and  
5 easy to use jar opener.

6 7. The invention as claimed in claim 1 wherein said opener has a predetermined  
7 operational direction so as to open and remove said cap said direction being push  
8 said present invention in a counter clockwise direction.

9

10

\* \* \* \* \*